

# ELASTIC DOUBLE LANYARD FITTED WITH ENERGY ABSORBER

ÉLASTIQUE LONGE DOUBLE AVEC ABSORBEUR D'ÉNERGIE  
CABO DE AMARRE ELÁSTICO CON ABSORBEDOR DE ENERGÍA  
DOUBLE LANYARD MIT BANDFALLDAMPFER

Code N° HAR016

June 2015

## DESCRIPTION

The elastic double lanyard is used as personnel protective equipment for people working at height. The lanyard has a length of 1 m when the elastic is retracted and 1,5 m when it's stretched (includes length of energy absorber and karabiners). This feature prevents the user step on the lanyard at short distances from the anchor point. After a fall, the energy absorber is deployed (the stitches break and the absorber unfolds). This double lanyard allows passing obstacles avoiding disconnection.



Compliant with EN355:2002 / EN354:1992 MADE IN EU



Notify body bearing the number 0082



Certification

## TECHNICAL SPECIFICATION

Comes with an installer and user manual.  
Material: 100% Polyamide



6 KN



> 22 KN



Code N°	Length	Availability
HAR016	1,5 m (2 m deployed)	Available from stock



If the lanyard has stopped a fall, the energy absorber is deployed and the lanyard must be discarded. Fallprotec makes available to its distributors maintenance manual for inspection and repair. In case of defects refer to maintenance manual and reject the lanyard if necessary. It is mandatory that a competent person checks the lanyard once a year. Not more than 1 person attached to the lanyard.

TEC0018-UK-Double Lanyard HAR016