

RANGE OF HARNESS

GAMME DE HARNAIS

GAMA DE ARNESES

PRODUKTPROGRAMM SICHERHEITSGURTE

Code N° HAR-R

June 2015

DESCRIPTION

Fallprotec has developed a range of quality harnesses and accessories to meet the latest requirements for this highly evolutionary market. Our innovation covers the distributions of forces on the body in the event of fall which protects sensitive areas of the body and decrease the risk of suspension trauma.



HAR001/002/003 Harness Prolight 2 anchor points automatic buckles.

It is comfortable in the event of fall. Its design offers freedom of movement and it's easy to don. Can be used occasionally in suspension. The straps under the seat are widened and padded. This harness has a light weight - just 750 gr for size L.



HAR020/021/022 Harness Tempo 2 anchor points.

It was developed for those who use a fall arrest harness occasionally, but without sacrificing its comfort and ease-of-use. It is comfortable in the event of fall. Its design offers freedom of movement and it's easy to don. Also, it offers 2 tool holders.



HAR005/006/057 Harness Urban 4 anchor points automatic buckles.

It has been developed to work in restrain with a positioning belt. It offers chest support when the user is sitting on a bosun chair, avoiding uncomfortable and painful abdominal pressure. The chair is attached by two side-adjustable straps.

TEC0025-UK-Range of Harness- HAR



HAR066/067/068 Multifunctional full body harness.

It is for rope access and rescue, it is the typical companion of many industrial climbers and service technicians. Its design offers freedom of movement, a lot of adjusting possibilities and its different anchorage and positioning rings allow an almost unlimited mobility and flexibility.



HAR069/070/071 Versatile 2 points harness with automatic buckles and extension back anchorage ring.

Equipped with simple CLICK buckles, it offers all the freedom in movement of, the buckles also allow a quick and easy dressing and undressing. The extension at the back anchorage ring allows an easier handling while using a SRL. This extension is also a good help for an additional mobility of the facade scaffolding builders.



HAR072/073/074 Elastic 2 points harness with automatic buckles

It is a very comfortable to wear harness. Its flexible webbing allows a very easy movement during the work without even feeling pressure or discomfort. The elastic harness is available with classic steel buckles and also with Click automatic buckles.

TEC0025-UK-Range of Harness- HAR

Code N°	Weight	Description	Normative	Availability
HAR020 HAR021 HAR022	0,64 kg	Harness Tempo 2 anchor points Sizes: M, L, XL	EN361	Available from stock
HAR001 HAR002 HAR003	0,7 kg	Harness Prolight 2 anchor points automatic buckles Sizes: M, L, XL Light harness easy to don	EN361	Available from stock
HAR005 HAR006 HAR057	0,9 kg	Harness Urban 4 anchor points automatic buckles Sizes: L, XL, XXL Side work position	EN361 EN358 EN813	Available from stock
HAR066 HAR067 HAR068	Kg	Multifunctional full body harness, polyester Sizes: S - M, L-XL, XL-XXL To work in suspension	EN361 EN358 EN813	Available from stock
HAR069 HAR070 HAR071	Kg	Versatile 2 points harness with automatic buckles and extension back anchorage ring Sizes: S - M, L-XL, XXL-XXXL Easy to don thanks to the automatic buckles	EN361	Available from stock
HAR072 HAR073 HAR074	Kg	Elastic 2 points harness with automatic buckles Sizes: S - M, L-XL, XXL-XXX Very comfortable harness and easy to don thanks to the elastic straps and automatic buckles	EN361	Available from stock



Before using the harness for the first time, it should be suitably adapted. The adaptation has to be made in a safe place to ensure the correct size, that there is adequate possibility for adjustment and that an acceptable level of comfort is achieved for the intended work. The harness must not be modified or supplemented using accessories other than those supplied by the manufacturer. Repairs or replacement of parts are strictly forbidden they may only be carried out by the manufacturer. The harness is designed for personal protection, all other usage is forbidden. Each user should have his own personal harness (read EN-365). It is important that the user makes a visual inspection of the equipment before use. The product must be replaced immediately if faults are discovered on the equipment In the event of uncertainty contact the dealer or the manufacturer for a professional inspection. The product must be immediately replaced if a fall has occurred when using the equipment. The inspection must be performed by a qualified person that has an inspection certificate and in accordance with the manufacturer's inspection procedures.

TEC0025-UK-Range of Harness- HAR